



- NOTES:
1. FURNISH ONE SET OF SIGN SUPPORTS FOR EACH SIGN.
  2. SEE NORTH CAROLINA DEPARTMENT OF TRANSPORTATION SIGN SPECIFICATION SUPPLEMENT FOR THE OF MATERIAL TO BE USED FOR SIGN SUPPORTS.
  3. FURNISH ALL MOUNTING HARDWARE.
  4. THE NORTH CAROLINA DEPARTMENT OF TRANSPORTATION WILL FURNISH SIGNS.
  5. USE ASTM A-36 STEEL GALVANIZED "U" BOLTS AND NUTS IN ACCORDANCE WITH ASTM A-153.
  6. USE ASTM A-36 ANCHOR BOLTS, GALVANIZED IN ACCORDANCE WITH ASTM A-153. OVERALL LENGTH OF ANCHOR BOLTS IS 686mm. ANCHOR BOLT PROJECTION, EMBEDMENT, AND HOOK TO BE AS SHOWN ON PLANS.  
OR,  
USE 16mm x 194mm DRILLED ADHESIVE ANCHOR GALVANIZED TO ASTM A-153. EACH ANCHOR SHALL BE PROVIDED WITH TWO (2) NUTS, ONE (1) FLAT WASHER, AND ONE (1) LOCK WASHER.

**Note:**  
This drawing is dimensioned in millimeters unless otherwise depicted within the drawing.